

BLOCKS- OVERHEAD CRANE



OVERHEAD BRIDGE CRANE BLOCKS

Wide capacity range, made to application, new or replacement

- Working loads from 15 tons to 300 tons
- Design factor 4:1 and up per specification
- All CMAA service classes (also FEM, DIN, ISO)
- Hooks are forged alloy in accord with DIN 15041 or 15402, single or duplex on thrust bearing and crosshead
- Hook lock or motorized hook available
- Fabricated, roll-formed or cast sheaves with roller bearings or bronze bushings
- · Optional lubrication through sheave shaft
- Heavy duty sheave guards
- Optional slotted covers over sheaves
- Special configurations, sheave spacings
- Optional insulated hook





See next page for Quote Request form... Miller Lifting Products 100A Sturbridge Rd. Charlton, MA 01507 USA T: +1.508.248.3941

E-mail: sales@millerproducts.net



OVERHEAD CRANE BLOCKS CUSTOM QUOTE REQUEST

Requestor name	Date	Quantity
Company & address		
Phone and E-mail address		
SHEAVES		
NUMBER OF SHEAVES: PITCH DIAMETER: _	OUTSIDE DIAMETER	l:
WIRE ROPE SIZE: NUMBER OF LINE PARTS	: EQUALIZER?	
ROLLER BEARING BRONZE BUSHING BLOCK CAPACITY & DIMENSIONS DIMENSIONS: A B C WORKING CAPACITY (LOAD LIMIT): (INDICATE US / METRIC TONS) DESIGN FACTOR: HOOK TYPE SINGLE DUPLEX LOCKING LOCKING HOOK INSULATED HOOK OTHER OTHER REQUIREMENTS CMAA SERVICE CLASS: SPECIAL TESTING, THIRD PARTY INSPECTION, OVERHALD SPECIAL TESTING, THIRD PARTY INSPECTION, OVERHALD OVERHALD DIMENSIONS B C	AUL WEIGHT, ETC:	SHEAVE SIZE